

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 962 196 A1**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**08.12.1999 Bulletin 1999/49**

(51) Int Cl.<sup>6</sup>: **A61F 2/16**

(21) Application number: **99304229.0**

(22) Date of filing: **01.06.1999**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventor: **Toop, Peter,**  
**Rayner Intraocular Lenses, Ltd.**  
**Hove, East Sussex BN3 7AN (GB)**


(74) Representative: **Perry, Robert Edward**  
**GILL JENNINGS & EVERY**  
**Broadgate House**  
**7 Eldon Street**  
**London EC2M 7LH (GB)**

(30) Priority: **01.06.1998 GB 9811746**

(71) Applicant: **Rayner Intraocular Lenses Limited**  
**Hove, East Sussex BN3 7AN (GB)**

**(54) Intraocular lens**

(57) An intraocular lens comprises an optic (1) and one or more curved haptics (3a, 3b) that can be compressed, in the plane of the lens, wherein the or each haptic is shaped such that, in a first stage of compression, the proximal part of the haptic can be fully compressed; in a second stage, the distal part of the haptic can be compressed to provide a lens that is essentially resistant to haptic failure.



**Fig. 1A**

**EP 0 962 196 A1**

## Description

### Field of the Invention

[0001] This invention relates to an intraocular lens.

### Background of the Invention

[0002] A typical intraocular lens comprises an optic and two opposed haptics. There are several constraints on the structure of such a lens. For example, while the haptics should maintain the optic centrally in the capsular sac, they should not be so springy as to damage the sac after insertion, in a folded state. Another important factor determining the form of suitable haptics is that they should be designed to resist excessive asymmetrical capsular contraction, while maintaining the optical performance of the lens, by preventing dislocation caused by buckling or twisting of the haptic or "haptic failure". While sufficient resistance can be provided by using rigid material, such a material is usually incompatible with the need to fold the lens, for insertion into the capsular sac following a small surgical incision.

[0003] WO-A-9741805 describes an intraocular implant comprising a substantially circular optic and two curved haptic loops. The distal end of each haptic rests on the internal wall of the eye. The optic and haptics are made of the same flexible material. This material has an elastic modulus of between 0.25 and 1 MPa. The width of each haptic decreases from its proximal end to its distal end, such that the ratio between the bending moment variation and the inertia moment variation at different points on the haptic is substantially constant. In a preferred embodiment, this is achieved by providing an aperture in each haptic; the width of the aperture generally decreases towards the distal end of the haptic.

### Summary of the Invention

[0004] According to the present invention, in an intraocular lens comprising an optic and one or more curved haptics which can be compressed in the plane of the lens, to provide a lens that is essentially resistant to haptic failure, the or each haptic is shaped such that there are at least two stages of compression. In the first stage, the proximal part of the or each haptic can be fully compressed. In the second stage of compression, the distal part can be compressed further.

[0005] Whereas in the first stage of compression, the haptic can be bent inwards with respect to a fulcrum defined by its point of attachment to the optic, a different fulcrum is established for the second stage. This may be the result of the haptic's interference with itself, or interference with the optic. There may be more than two stages of compression, and the number may be such that the effect is continuous, i.e. as in a rolling action where the degree of compression is related to distance from the haptic's point of attachment to the optic.

[0006] An intraocular lens according to the present invention is such that its overall size can be reduced by compression against a spring-like resistance of the haptic, sufficient to maintain centration in the capsule. Following the second or a further stage of compression, when the distal end of the haptic is in contact with the lens body, the lens is deformed (in profile) to a shape that is highly resistant to twisting or buckling.

[0007] In a preferred embodiment, the intraocular lens according to the present invention comprises two opposed, curved haptics. In such an embodiment, the lens is deformed to a circular, oval or elliptical shape.

### Description of the Invention

[0008] The invention will now be described by way of example only with reference to the accompanying drawings, in which:

Figures 1a and 1b are respectively plan and side views of an intraocular lens embodying the present invention;

Figure 2 is a side view of a lens which has undergone haptic failure due to capsular shrinkage; and Figures 3 and 4 are plan views of the lens of Fig. 1, after respectively the first and second stages of compression.

[0009] The intraocular lens shown in Fig. 1 comprises a generally circular optic 1 having convex faces 2a and 2b. The lens also comprises haptics 3a and 3b each joined to the optic. Each haptic includes an aperture 4a, 4b.

[0010] Each haptic is joined to the optic in generally conventional manner. Fig. 1a shows dimensions A and B at the joining; typically,  $A > B$ .

[0011] The outside of the proximal part of each haptic and the inner side of its distal part are defined with respect to the aperture by walls of similar width C and D. Each aperture is of substantially constant width. A more important characteristic of each aperture is its overall shape, including opposed points 5 and 6 which, as described below, can be brought into contact, and effectively define not only a bend in the aperture but also the boundary between proximal and distal parts of the haptic.

[0012] As shown in Fig. 2, when there is shrinkage of the capsular sac 7, the haptic is liable to buckle along the line B of Fig. 1. The shape of the haptic and aperture according to the present invention minimise the likelihood of this occurrence.

[0013] Figs. 3 and 4 each show the essentially elliptical form (8a and 8b) of the lens shown in Fig. 1, when partially and fully compressed, respectively.

[0014] More particularly, Fig. 3 shows that initial compression of the haptic leads to abutment of opposite walls of the aperture, bringing points 5 and 6 into contact and thereby defining a proximal part that is fully com-

pressed and a distal part that can undergo further compression. As shown in Fig. 4, such further compression brings the distal end of the haptic substantially into contact with the periphery of the optic, to give an essentially elliptical shape, in plan. This design allows the overall size of the intraocular lens to be reduced, by the spring-like resistance of the haptic, sufficient to maintain centration in the capsule.

**[0015]** Following the first stage of compression, further contraction is prevented in one meridian by interference of one part of the haptic with an adjacent part, and/or with the lens body. Along this meridian, asymmetrical capsular contraction is subsequently prevented. This spring-like resistance of the haptic is then stiffened by the new fulcrum created by the haptic's interference with itself and/or with the lens body. This additional stiffness allows for some further contraction of the capsule along the adjacent meridians, and has the effect of preventing the contraction force along the fixed 10 mm meridian reaching a level sufficient to buckle the haptic. Ultimately, under severe capsular contraction, the distal haptic ends reached the lens body, at which point the lens is deformed (in profile) to the illustrated elliptical shape. This is highly resistant to twisting or buckling.

**[0016]** By way of example, initial contraction may be to dimensions of 10 mm x 8 mm (see Fig. 3). Further contraction gives dimensions of 9.5 mm x 7.5 mm (see Fig. 4).

**[0017]** The thickness of the or each haptic (e.g. the dimension E shown in Fig. 1b) may be greater than that of conventional lenses. For example, haptics of conventional lenses may be 0.3 mm thick. The or each haptic in the present invention may be at least 0.6 mm thick. Such thicker haptics may help to reduce or avoid damage to the lens when it is inserted using a typical lens applicator. Thicker haptics may also advantageously separate anterior and posterior capsule surfaces, which can reduce migration and proliferation of lens epithelial cells from the anterior capsule surface onto the posterior capsule surface.

## Claims

1. An intraocular lens comprising an optic (1) and one or more curved haptics (3a, 3b) that can be compressed, in the plane of the lens, wherein the or each haptic is shaped such that, in a first stage of compression, the proximal part of the haptic can be fully compressed; in a second stage, the distal part of the haptic can be compressed to provide a lens that is essentially resistant to haptic failure.
2. A lens according to claim 1, wherein the or each haptic includes an aperture (4a, 4b) of which opposed points (5, 6) are brought into contact, in the first stage of compression.
3. A lens according to claim 1 or claim 2, wherein the or each stage of compression is essentially continuous, full compression being reached gradually from the proximal end towards the distal end of the haptic.
4. A lens according to any preceding claim, which comprises two or more haptics and wherein the haptics are compressed to provide an essentially elliptical form (8b) of the lens.
5. A lens according to any preceding claim, wherein the or each haptic is at least 0.6 mm thick.




Fig. 1A




Fig. 1B




Fig. 2




Fig. 3




Fig. 4



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 99 30 4229

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	WO 87 01931 A (M.J. TILLAY) 9 April 1987 (1987-04-09) * page 10, line 30 - page 15, line 28; figures 1-3 *	1,3,4	A61F2/16
X	US 5 133 749 A (L. T. JORDAN) 28 July 1992 (1992-07-28) * abstract; figures *	1,3,4	
X	WO 97 20523 A (ALCON LABORATORIES) 12 June 1997 (1997-06-12) * page 3, line 26 - page 4, line 9; figures *	1,4,5	
D,A	WO 97 41805 A (W.K.ET ASSOCIÉS) 13 November 1997 (1997-11-13) * page 7, line 15 - page 8, line 12; figures 2A,2B,4A,4B *	1,2	
A	EP 0 766 952 A (RAYNER INTRAOCULAR LENSES LTD ET AL.) 9 April 1997 (1997-04-09) * abstract *	2	
A	US 4 787 904 A (S.L. SEVERIN ET AL.) 29 November 1988 (1988-11-29) * column 2, line 32 - line 37; figures 1,2 *	1,2	
A	EP 0 215 468 A (G. FROMBERG ET AL.) 25 March 1987 (1987-03-25) * page 5, line 7 - line 10; figures 1,2 *	5	A61F
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 16 September 1999	Examiner Wolf, C
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/92 (P/M/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 4229

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

16-09-1999

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
WO 8701931	A	09-04-1987	US	4666445 A	19-05-1987
			EP	0238634 A	30-09-1987
US 5133749	A	28-07-1992	NONE		
WO 9720523	A	12-06-1997	US	5716403 A	10-02-1998
			AT	180960 T	15-06-1999
			AU	700206 B	24-12-1998
			AU	7470496 A	27-06-1997
			CA	2239091 A	12-06-1997
			DE	69602853 D	15-07-1999
			EP	0865261 A	23-09-1998
			JP	10513099 T	15-12-1998
WO 9741805	A	13-11-1997	FR	2748200 A	07-11-1997
			CA	2253359 A	13-11-1997
			EP	0897294 A	24-02-1999
EP 766952	A	09-04-1997	NONE		
US 4787904	A	29-11-1988	NONE		
EP 215468	A	25-03-1987	DE	3532928 A	02-04-1987

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82